

### **CLIENT / CUSTOMER REQUIRING MOVING OF LOAD**

### **CONTRACT LIFT**

#### **HIRED LORRY LOADER**

#### The Client must:

Carry out all work in aaccordance with BS 7121

Supply the Appointed Person

Plan the lift and operate a safe system of work

Ensure that line lorry loader hired is of a suitable type and capacity

Check the credentials of the lorry loader hire company and certification suppled

Ensure the the ground conditions are assed and that stabiliser loads are adequately spread to ensure the ground bearing capacity is not exceeded

## The lorry loader owner has a duty to:

Provide a lorry loader that is properly maintained, tested and certified

Provide a competent operator

Confirm to the customer the size of standard spreader pads supplied with the lorry loader.

FORMALLY CONTRACTED or Included with the delivery of goods to a non-domestic customer

### **The Client must:**

Specify that all work is to be accordance with BS 7121

Specify the contractor is to supply an Appointed Person

Provide information on the ground bearing capacity of the lifting area

Confirm what other information and/or services will be provided to the Contractor by the Customer

### The Lifting Contractor is responsible for:

Supplying the Appointed Person

Planning the lift and operation of a safe system of work

Organisation and control of the lifting operation

Providing a lorry loader that is properly maintained, tested and certified

Providing a competent operator

Ensuring stabiliser loads are adequately spread to ensure the ground bearing capacity is not exceededsupplied with the lorry loader.

Included with the delivery of goods to a domestic customer

# The Lifting Contractor is responsible for

Ensuring that all work is to be accordance with BS 7121

Supplying the Appointed Person

Ensuring that adequate information regarding site conditions is obtained

Planning the lift and operation of a safe system of work

Organisation and control of the lifting operation

Providing a lorry loader that is properly maintained, tested and certified

Providing a competent operator

Ensure the the ground conditions are assed and that stabiliser loads are adequately spread to ensure the ground bearing capacity is not exceeded